

Tracking (SARSAT) earth stations operating in the 1544–1545 MHz band for any ATC base station located either within 27 km of a SARSAT station, or within radio horizon of the SARSAT station, whichever is less.

(2) Take all practicable steps to avoid locating ATC base stations within radio line of sight of Mobile Aeronautical Telemetry (MAT) receive sites in order to protect U.S. MAT systems consistent with ITU-R Recommendation ITU-R M.1459. MSS ATC base stations located within radio line of sight of a MAT receiver must be coordinated with the Aerospace and Flight Test Radio Coordinating Council (AFTRCC) for non-Government MAT receivers on a case-by-case basis prior to operation. For government MAT receivers, the MSS licensee shall supply sufficient information to the Commission to allow coordination to take place. A listing of current and planned MAT receiver sites can be obtained from AFTRCC for non-Government sites and through the FCC's IRAC Liaison for Government MAT receiver sites.

(g) ATC mobile terminals shall:

(1) Be limited to a peak EIRP level of 0 dBW and an out-of-channel emissions of -67 dBW/4 kHz at the edge of an MSS licensee's authorized and internationally coordinated MSS frequency assignment.

(2) Be operated in a fashion that takes all practicable steps to avoid causing interference to U.S. radio astronomy service (RAS) observations in the 1660–1660.5 MHz band.

(3) Not generate EIRP density, averaged over any two-millisecond active transmission interval, greater than -70 dBW/MHz in the 1559–1605 MHz band or greater than a level determined by linear interpolation in the 1605–1610 MHz band, from -70 dBW/MHz at 1605 MHz to -46 dBW/MHz at 1610 MHz. The EIRP, averaged over any two-millisecond active transmission interval, of discrete out-of-band emissions of less than 700 Hz bandwidth from such mobile terminals shall not exceed -80 dBW in the 1559–1605 MHz band or exceed a level determined by linear interpolation in the 1605–1610 MHz band, from -80 dBW at 1605 MHz to -56 dBW at 1610 MHz. The EIRP density of carrier-off-state emissions

from such mobile terminals shall not exceed -80 dBW/MHz in the 1559–1610 MHz band, averaged over a two-millisecond interval. A root-mean-square detector function with a resolution bandwidth of one megahertz or equivalent and no less video bandwidth shall be used to measure wideband EIRP density for purposes of this rule, and narrowband EIRP shall be measured with a root-mean-square detector function with a resolution bandwidth of one kilohertz or equivalent.

(h) When implementing multiple base stations and/or base stations using multiple carriers, where any third-order intermodulation product of these base stations falls on an L-band MSS band coordinated for use by another MSS operator with rights to the coordinated band, the MSS ATC licensee must notify the MSS operator. The MSS operator may request coordination to modify the base station carrier frequencies, or to reduce the maximum base station EIRP on the frequencies contributing to the third-order intermodulation products. The threshold for this notification and coordination is when the sum of the calculated signal levels received by an MSS receiver exceeds -70 dBm. The MSS receiver used in these calculations can be assumed to have an antenna with 0 dBi gain. Free-space propagation between the base station antennas and the MSS terminals can be assumed and actual signal polarizations for the ATC signals and the MSS system may be used.

[70 FR 19319, Apr. 13, 2005]

§ 25.254 Special requirements for ancillary terrestrial components operating in the 1610–1626.5 MHz/2483.5–2500 MHz bands.

(a) An applicant for an ancillary terrestrial component in these bands must demonstrate that ATC base stations shall:

(1) Not exceed a peak EIRP of 32 dBW in 1.25 MHz;

(2) Not cause unacceptable interference to systems identified in paragraph (c) of this section and, in any case, shall not exceed out-of-channel emissions of -44.1 dBW/30 kHz at the edge of the MSS licensee's authorized frequency assignment;

(3) At the time of application, that it has taken, or will take steps necessary to avoid causing interference to other services sharing the use of the 2450-2500 MHz band through frequency coordination; and

(4) Base stations operating in frequencies above 2483.5 MHz shall not generate EIRP density, averaged over any two-millisecond active transmission interval, greater than -70 dBW/MHz in the 1559-1610 MHz band. The EIRP, averaged over any two-millisecond active transmission interval, of discrete out-of-band emissions of less than 700 Hz bandwidth from such base stations shall not exceed -80 dBW in the 1559-1610 MHz band. A root-mean-square detector function with a resolution bandwidth of one megahertz or equivalent and no less video bandwidth shall be used to measure wideband EIRP density for purposes of this rule, and narrowband EIRP shall be measured with a root-mean-square detector function with a resolution bandwidth of one kilohertz or equivalent.

(b) An applicant for an ancillary terrestrial component in these bands must demonstrate that mobile terminals shall:

(1) Meet the requirements contained in §25.213 to protect radio astronomy service (RAS) observations in the 1610.6-1613.8 MHz band from unacceptable interference;

(2) Observe a peak EIRP limit of 1.0 dBW in 1.25 MHz;

(3) Observe an out-of-channel EIRP limit of -57.1 dBW/30 kHz at the edge of the licensed MSS frequency assignment.

(4) ATC mobile terminals operating in assigned frequencies in the 1610-1626.5 MHz band shall not generate EIRP density, averaged over any two-millisecond active transmission interval, greater than -70 dBW/MHz in the 1559-1605 MHz band or greater than a level determined by linear interpolation in the 1605-1610 MHz band, from -70 dBW/MHz at 1605 MHz to -10 dBW/MHz at 1610 MHz. The EIRP, averaged over any two-millisecond active transmission interval, of discrete out-of-band emissions of less than 700 Hz bandwidth from such mobile terminals shall not exceed -80 dBW in the 1559-1605 MHz band or exceed a level deter-

mined by linear interpolation in the 1605-1610 MHz band, from -80 dBW at 1605 MHz to -20 dBW at 1610 MHz. The EIRP density of carrier-off-state emissions from such mobile terminals shall not exceed -80 dBW/MHz in the 1559-1610 MHz band, averaged over a two-millisecond interval. A root-mean-square detector function with a resolution bandwidth of one megahertz or equivalent and no less video bandwidth shall be used to measure wideband EIRP density for purposes of this rule, and narrowband EIRP shall be measured with a root-mean-square detector function with a resolution bandwidth of one kilohertz or equivalent.

(c) Applicants for an ancillary terrestrial component to be used in conjunction with a mobile-satellite service system using CDMA technology shall coordinate the use of the Big LEO MSS spectrum designated for CDMA systems using the framework established by the ITU in Recommendation ITU-R M.1186 "Technical Considerations for the Coordination Between Mobile Satellite Service (MSS) Networks Utilizing Code Division Multiple Access (CDMA) and Other Spread Spectrum Techniques in the 1-3 GHz Band" (1995). Recommendation ITU-R M.1186 is incorporated by reference. The Director of the Federal Register approves this incorporation by reference in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. Copies of this standard can be inspected at the Federal Communications Commission, 445 12th Street, SW., Washington, DC (Reference Information Center) or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html. The ITU-R Recommendations can also be purchased from the International Telecommunication Union (ITU), Place des Nations, CH-1211 Geneva 20, Switzerland.

NOTE TO §25.254: The preceding rules of §25.254 are based on cdma2000 and IS-95 system architecture. To the extent that a Big LEO MSS licensee is able to demonstrate that the use of different system architectures would produce no greater potential interference than that produced as a result of implementing the rules of this section, an

§ 25.255

MSS licensee is permitted to apply for ATC authorization based on another system architecture.

[68 FR 33653, June 5, 2003, as amended at 69 FR 18803, Apr. 9, 2004; 70 FR 19320, Apr. 13, 2005]

§ 25.255 Procedures for resolving harmful interference related to operation of ancillary terrestrial components operating in the 1.5/1.6 GHz, 1.6/2.4 GHz and 2 GHz bands.

If harmful interference is caused to other services by ancillary MSS ATC operations, either from ATC base stations or mobile terminals, the MSS ATC operator must resolve any such interference. If the MSS ATC operator claims to have resolved the interference and other operators claim that interference has not been resolved, then the parties to the dispute may petition the Commission for a resolution of their claims.

[68 FR 33653, June 5, 2003]

§ 25.256 Special Requirements for operations in the 3.65–3.7 GHz band.

Upon request from a terrestrial licensee authorized under Subpart Z, Part 90 that seeks to place base and fixed stations in operation within 150 km of a primary earth station, licensees of earth stations operating on a primary basis in the fixed satellite service in the 3.65–3.7 GHz band must negotiate in good faith with that terrestrial licensee to arrive at mutually agreeable operating parameters to prevent unacceptable interference.

[70 FR 24725, May 11, 2005]

§ 25.257 Special requirements for operations in the band 29.1–29.25 GHz between NGSO MSS and LMDS.

(a) Non-geostationary mobile satellite service (NGSO MSS) operators shall be licensed to use the 29.1–29.25 GHz band for Earth-to-space transmissions from feeder link earth station complexes. A “feeder link earth station complex” may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by a NGSO MSS licensee or applicants pursuant to § 101.147.

47 CFR Ch. I (10–1–07 Edition)

(b) A maximum of seven (7) feeder link earth station complexes in the contiguous United States, Alaska and Hawaii may be placed into operation, in the largest 100 MSAs, in the band 29.1–29.25 GHz in accordance with § 25.203 and § 101.147 of this chapter.

(c) One of the NGSO MSS operators licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of eight feeder link earth station complexes that transmit in the 29.1–29.25 GHz band. The other NGSO MSS operator licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of two feeder link earth station complexes that transmit in the 29.1–29.25 GHz band.

(d) Additional NGSO MSS operators may be licensed in this band if the additional NGSO MSS operator shows that its system can share with the existing NGSO MSS systems.

(e) All NGSO MSS operators shall cooperate fully and make reasonable efforts to identify mutually acceptable locations for feeder link earth station complexes. In this connection, any single NGSO MSS operator shall only identify one feeder link earth station complex protection zone in each category identified in § 101.147(c)(2) of this chapter until the other NGSO MSS operator has been given an opportunity to select a location from the same category.

[61 FR 44181, Aug. 28, 1996]

§ 25.258 Sharing between NGSO MSS Feeder links Stations and GSO FSS services in the 29.25–29.5 GHz Bands.

(a) Operators of NGSO MSS feeder link earth stations and GSO FSS earth stations in the band 29.25 to 29.5 GHz where both services have a co-primary allocation shall cooperate fully in order to coordinate their systems. During the coordination process both service operators shall exchange the necessary technical parameters required for coordination.

(b) Licensed GSO FSS systems shall, to the maximum extent possible, operate with frequency/polarization selections, in the vicinity of operational or planned NGSO MSS feeder link earth station complexes, that will minimize